#### SUBCHAPTER 21. REQUIREMENTS FOR INDIRECT USERS

#### 7:14A-21.1 Purpose and scope

- (a) This subchapter establishes requirements to:
  - 1. Establishes requirements to prevent the introduction of pollutants into a local agency's treatment works which may:
    - i. Interfere with the operation of the local agency's treatment works;
    - ii. Pass through or would otherwise be incompatible with the local agency's treatment works; or
    - iii. Interfere with the local agency's chosen method of sludge management;
  - 2. Sets forth the minimum discharge criteria and reporting requirements for all indirect users: and
  - 3. Sets forth the specific requirements for an individual NJPDES-SIU permit for a significant indirect user as defined in N.J.A.C. 7:14A-1.2 discharging into a non-delegated local agency's treatment works.
- (b) The Department adopts and incorporates herein by reference the General Pretreatment Regulations for Existing and New Sources of Pollution, 40 CFR 403, and National Pretreatment Standards in 40 CFR chapter I, subchapter N, as amended and supplemented.

#### 7:14A-21.2 Minimum requirements for all indirect users

- (a) The following conditions apply to all indirect users:
  - 1. The prohibitions, as set forth in 40 CFR Part 403.5, against the introduction into a local agency's treatment works any of the following:
    - i. Any pollutant(s) which causes pass through or interference;
    - ii. Any pollutants which create a fire or explosion hazard in the local agency's treatment works including, but not limited to, wastestreams with a closed cup flashpoint of less than 140 degrees Fahrenheit or 60 degrees Centigrade using the test methods specified in 40 CFR 261.21;
    - iii. Any pollutants which will cause corrosive structural damage to

the local agency's treatment works, but in no case a discharge with pH lower than 5.0, unless the treatment works is specifically designed to accommodate such discharges;

- iv. Any solid or viscous pollutants in amounts which will cause obstruction to the flow in the local agency's treatment works resulting in interference;
- v. Any pollutant, including oxygen demanding pollutants (for example, BOD) released in a discharge at a flow rate and/or pollutant concentration which will cause interference with the local agency's treatment works;
- vi. Heat in amounts which will inhibit biological activity at the local agency's treatment works resulting in interference, but in no case heat in such quantities that the temperature at the local agency's treatment works exceeds 40 degrees Celsius (104 degrees Fahrenheit) unless the Department, upon request of the local agency, approves alternative temperature limits;
- vii. Petroleum oil, nonbiodegradable cutting oil, or any product of mineral oil origin in amounts that will cause interference or pass through;
- viii. Any pollutants which result in the presence of toxic gases, vapors, or fumes within the local agency's treatment works in a quantity that may cause acute worker health and safety problems; or
- ix. Any trucked or hauled pollutant, except at discharge points designated by the local agency.
- 2. The State pretreatment standards for petroleum hydrocarbons pursuant to N.J.A.C. 7:14A-12; and
- 3. Local limits developed by the local agency pursuant to N.J.A.C. 7:14A-19.7.
- (b) All indirect users shall notify the local agency immediately of all discharges that could cause problems to the local agency's treatment works, including any slug discharge loading.
- (c) The penalties, including mandatory minimum penalties, and the settlement restrictions applicable to any civil administrative penalty assessment, as specified under N.J.A.C. 7:14-8, are fully applicable to violations by indirect users occurring on or after January 19, 1999.

#### 7:14A-21.3 Additional requirements for all significant indirect users

- (a) Within 60 days after the effective date of a pretreatment standard for a subcategory under which an indirect user may be included, the indirect user may request that the control authority provide written determination on whether the indirect user falls within that particular subcategory. If an existing indirect user adds or changes a process or operation which may be included in a subcategory, the existing indirect user shall request this determination prior to commencing discharge from the added or changed process or operation. A new source shall request this determination prior to commencing discharge. Each request shall include:
  - 1. A description of which subcategories might be applicable;
  - 2. Evidence and reasons why a particular subcategory is applicable and why others are not applicable; and
  - 3. The following certification over the signature of the person submitting the request:
    - "I certify under penalty of law that this document and all attachments were prepared under my direction or supervision in accordance with a system designed to assure that qualified personnel properly gather and evaluate the information submitted. Based on my inquiry of the person or persons who manage the system, or those persons directly responsible for gathering the information, the information submitted is, to the best of my knowledge and belief, true, accurate, and complete. I am aware that there are significant penalties for submitting false information, including the possibility of fine and imprisonment for knowing violations."
- (b) Within 180 days after the effective date of a categorical pretreatment standard or 180 days after the final decision by the control authority on the categorical determination request submitted under (a) above, whichever is later, each existing indirect user subject to a categorical pretreatment standard and currently discharging or scheduled to discharge to a local agency shall submit to the control authority a baseline report. The baseline report shall contain the information specified in (b)1 through 7 below. New sources and sources that became users subsequent to the promulgation of an applicable categorical standard shall submit the information specified in (b)1 through 5 below.
  - 1. Identifying information, specifically the name and address of the facility and including the name of the operator and owners;
  - 2. A list of any environmental control permits held by or for the facility;

- 3. A brief description of the nature, average rate of production, and Standard Industrial Classification of the operation(s) carried out by such indirect user. This description shall include a schematic process diagram which indicates points of discharge to the local agency from the regulated processes;
- 4. Information showing the measured average daily and maximum daily flow, in gallons per day, to the local agency's treatment works from each of the following:
  - i. Regulated process streams; and
  - ii. Other streams as necessary to allow use of the combined wastestream formula of N.J.A.C. 7:14A-21.4(c). The control authority may accept verifiable estimates of these flows instead of measured flows where justified by cost or feasibility considerations;
- 5. Pollutant levels measured as follows:
  - i. The indirect user shall identify the pretreatment standards applicable to each regulated process;
  - ii. The indirect user shall submit the results of sampling and analysis identifying the nature and concentration (or mass, where required by the standard or control authority) of regulated pollutants in the discharge from each regulated process. Both daily maximum and average concentration (or mass, where required) shall be reported. The sample shall be representative of daily operations;
  - iii. A minimum of four grab samples shall be used for pH, cyanide, total phenols, oil and grease, sulfide, and volatile organics. For all other pollutants, 24-hour composite samples shall be obtained through flow-proportional composite sampling techniques where feasible. The control authority shall waive flow-proportional composite sampling for any indirect user that demonstrates that flow-proportional sampling is infeasible. In such cases, samples shall be obtained through time-proportional composite sampling techniques or through a minimum of four grab samples where the indirect user demonstrates that this shall provide a representative sample of the effluent being discharged;
  - iv. The indirect user shall take a minimum of one representative sample to compile data necessary to comply with the requirements of this paragraph;

- v. Samples shall be taken immediately downstream from pretreatment facilities if such exist or immediately downstream from the regulated process if no pretreatment exists. If other wastewaters are mixed with the regulated wastewater prior to pretreatment the indirect user shall measure the flows and concentrations necessary to allow use of the combined wastestream formula of N.J.A.C. 7:14A-21.4(c) in order to evaluate compliance with the pretreatment standards. Where an alternative concentration or mass limit has been calculated in accordance with N.J.A.C. 7:14A-21.4(c) this adjusted limit along with supporting data shall be submitted to the control authority;
- vi. Sampling and analysis shall be performed in accordance with the techniques prescribed in 40 CFR Part 136 and amendments thereto. Where 40 CFR Part 136 does not contain sampling or analytical techniques for the pollutant in question, or where the Department determines that the 40 CFR Part 136 sampling and analytical techniques are inappropriate for the pollutant in question, sampling and analysis shall be performed using validated analytical methods or any other applicable sampling and analytical procedures, including procedures suggested by the local agency or other parties, approved by the Department;
- vii. The control authority may allow the submission of a baseline report which utilizes only historical data so long as the data are sufficient to determine the need for industrial pretreatment measures; and
- viii. The baseline report shall indicate the time, date and place, of sampling, and methods of analysis, and shall contain a certification from an authorized representative that such sampling and analysis is representative of normal work cycles and expected pollutant discharges to the local agency's treatment works:
- 6. A statement, reviewed by an authorized representative of the indirect user and certified to by a qualified professional, as to whether pretreatment standards are being met on a consistent basis, and, if not, whether additional operation and maintenance and/or additional pretreatment is required for the indirect user to meet the pretreatment standards and requirements; and
- 7. If additional pretreatment and/or operation and maintenance shall be required to meet the pretreatment standards, the shortest compliance schedule under which the indirect user shall provide such additional pretreatment and/or operation and maintenance shall be submitted. The completion date in this schedule shall not be later than the compliance

date established for the applicable pretreatment standard.

- i. Where the indirect user's categorical pretreatment standard has been modified by the combined wastestream formula pursuant to N.J.A.C. 7:14A-21.4(c) and/or a fundamentally different factors variance pursuant to N.J.A.C. 7:14A-21.5 at the time the indirect user submits the baseline report required under this subsection, the information required under (b)6 above and this paragraph shall pertain to the modified limits;
- ii. If the categorical pretreatment standard is modified by the combined wastestream formula pursuant to N.J.A.C. 7:14A-21.4(c) and/or a fundamentally different factors variance pursuant to N.J.A.C. 7:14A-21.5 after the indirect user submits the baseline report required under this subsection, any necessary amendments to the information required under (b)6 above and this paragraph shall be submitted by the indirect user to the control authority within 60 days after the modified limit is approved.
- (c) Existing sources shall comply with categorical pretreatment standards within three years of the date the standard is effective unless a sooner compliance deadline is specified in the applicable subpart of 40 CFR chapter I, subchapter N. Existing sources which become indirect users subsequent to promulgation of an applicable categorical pretreatment standard shall be considered existing indirect users except where such sources meet the definition of a "new source" under N.J.A.C. 7:14A-1.2. New sources shall install and have in operating condition, and shall "start-up" all pollution control equipment required to meet applicable pretreatment standards, before beginning to discharge. Within the shortest feasible time, not to exceed 90 days from commencement of discharge, new sources shall meet all applicable pretreatment standards.
- (d) As conditions to any compliance schedule for meeting categorical pretreatment standards pursuant to (b)7 above, the indirect user shall:
  - 1. Incorporate in the compliance schedule increments of progress described as dates for the commencement and completion of milestones in the construction and operation of additional pretreatment as required for the indirect user to meet the applicable categorical pretreatment standards (for example, hiring an engineer, completing preliminary plans, completing final plans, executing contract for major components, commencing construction, completing construction). No such increment shall exceed nine months; and
  - 2. Not later than 14 days following each date in the compliance schedule and the final date for compliance, submit a progress report to the

control authority including, at a minimum, whether or not the indirect user met the increment of progress on such date and, if not, the anticipated date of compliance with such increment of progress, the reason for delay, and the steps being taken by the indirect user to resume the construction schedule established. In no event shall more than nine months elapse between such progress reports to the control authority.

- (e) Within 90 days following the date for final compliance with applicable categorical pretreatment standards or, in the case of a new source, within 90 days following commencement of the introduction of wastewater into the local agency's treatment works, any indirect user subject to pretreatment standards and requirements shall submit to the control authority a report containing the information described in (b)4 through 6 above. For indirect users subject to equivalent mass or concentration limits established by the control authority in accordance with the procedures in N.J.A.C. 7:14A-21.4(c), this report shall contain a reasonable measure of the indirect user's long term production rate. For all other indirect users subject to categorical pretreatment standards expressed in terms of allowable pollutant discharge per unit of production (or other measure of operation), this report shall include the indirect user's actual production during the appropriate sampling period.
- (f) Periodic reports on continued compliance shall be submitted as follows:
  - 1. Any indirect user subject to a categorical pretreatment standard, after the compliance date of such pretreatment standard, or, in the case of a new source, after commencement of the discharge into the local agency, shall submit to the control authority during the months of June and December, unless required more frequently in the pretreatment standard or by the control authority or the Department, a report indicating the nature and concentration of pollutants in the effluent which are limited by such categorical pretreatment standards. This report shall include a record of measured or estimated average and maximum daily flows for the reporting period for the discharge reported in (b)4 above except that the control authority may require more detailed reporting of flows. At the discretion of the control authority and in consideration of such factors as local high or low flow rates, holidays, and budget cycles, the control authority may approve the designation of months other than June and December during which the above reports are to be submitted.
  - 2. Where the control authority has imposed mass limitations on indirect users as provided for by N.J.A.C. 7:14A-21.4(c), the report required under (f)1 above shall indicate the mass of pollutants regulated by pretreatment standards in the discharge from the indirect user.

- 3. For indirect users subject to equivalent mass or concentration limits established by the control authority in accordance with the procedures in N.J.A.C. 7:14A-21.4(a), the report required under (f)1 above shall contain a reasonable measure of the indirect user's long term production rate. For all other indirect users subject to categorical pretreatment standards expressed only in terms of allowable pollutant discharge per unit of production (or other measure of operation), the report required under (f)1 above shall include the indirect user's actual average production rate for the reporting period.
- (g) Monitoring and analysis to demonstrate continued compliance shall be conducted as follows:
  - 1. The reports required under (b), (e) and (f) above shall contain the results of sampling and analysis of the discharge, including the flow and the nature and concentration, or production and mass where requested by the control authority, of pollutants contained therein which are limited by the applicable pretreatment standards. This sampling and analysis may be performed by the control authority in lieu of the indirect user. Where the control authority performs the required sampling and analysis in lieu of the indirect user, the indirect user will not be required to submit the compliance certification required under (b)6 and (e) above. In addition, where the control authority itself collects all the information required for the report, including flow data, the indirect user will not be required to submit the report required under (b), (e) and (f) above.
  - 2. If sampling performed by an indirect user indicates a violation of pretreatment standards, the indirect user shall notify the control authority within 24 hours of becoming aware of the violation. The indirect user shall repeat the sampling and analysis and submit the results of the repeat analysis to the control authority within 30 days after becoming aware of the violation, except the indirect user is not required to resample if:
    - i. The control authority conducts sampling of the indirect user's discharge at a frequency of at least once per month; or
    - ii. The control authority conducts sampling of the indirect user's discharge between the time when the indirect user performs its initial sampling and the time when the indirect user receives the results of this sampling.
  - 3. The reports required under (f) above shall be based upon data obtained through appropriate sampling and analysis performed during the period covered by the report, which data are representative of conditions occurring during the reporting period. The control authority shall

- require that frequency of monitoring necessary to assess and ensure compliance by indirect users with applicable pretreatment standards and requirements.
- 4. All analyses shall be performed in accordance with procedures contained in 40 CFR Part 136, as amended, or with any other test procedures approved by the Department. Sampling shall be performed in accordance with the techniques approved by the Department. Where 40 CFR Part 136 does not include sampling or analytical techniques for the pollutants in question, or where the Department determines that the 40 CFR Part 136 sampling and analytical techniques are inappropriate for the pollutant in question, sampling and analyses shall be performed using validated analytical methods or any other sampling and analytical procedures, including procedures suggested by the control authority, local agency or the indirect user, approved by the Department.
- 5. If an indirect user subject to the reporting requirement in (f) above monitors any pollutant more frequently than required by the control authority, using the procedures prescribed in (g)4 above, the results of this monitoring shall be included in the report.
- (h) Significant indirect users as defined in N.J.A.C. 7:14A-1.2 shall submit to the control authority at least once each month (on dates specified by the control authority) a description of the nature, concentration, and flow of the pollutants required by the control authority to be reported. These reports shall be based on sampling and analysis performed in the period covered by the report, and in accordance with the techniques described in 40 CFR Part 136, as amended. Where 40 CFR Part 136 does not contain sampling or analytical techniques for the pollutant in question, or where the Department determines that the 40 CFR Part 136 sampling and analytical techniques are inappropriate for the pollutant in question, sampling and analysis shall be performed using validated analytical methods or any other applicable sampling and analytical procedures, including procedures suggested by the control authority, local agency or the indirect user, approved by the Department. This sampling and analysis may be performed by the control authority in lieu of the significant indirect user. Where the control authority itself collects all the information required for the report, the indirect user will not be required to submit the report.
- (i) Requirements for notification regarding hazardous waste are as follows:
  - 1. The indirect user shall notify the local agency, the USEPA Regional Waste Management Division Director, and the Department's Division of Solid and Hazardous Waste in writing of any discharge into the local agency's treatment works of a substance, which, if otherwise disposed of, would be a hazardous waste under 40 CFR Part 261. Such notification shall include the name of the hazardous waste as set forth

in 40 CFR Part 261, the USEPA hazardous waste number, and the type of discharge (continuous, batch, or other). If the indirect user discharges more than 100 kilograms of such waste per calendar month to the local agency's treatment works, the notification shall also contain the following information to the extent such information is known and readily available to the indirect user: an identification of the hazardous constituents contained in the wastes, an estimation of the mass and concentration of such constituents in the wastestream discharged during that calendar month, and an estimation of the mass of constituents in the wastestream expected to be discharged during the following 12 months. Indirect users who commence discharging after the effective date of this chapter shall provide the notification no later than 180 days after the discharge of the listed or characteristic hazardous waste. Any notification under this paragraph need be submitted only once for each hazardous waste discharged. However, notification of changed discharges must be submitted under (j) below. The notification requirement in this section does not apply to pollutants already reported under the self-monitoring requirements of (b), (e) and (f) above.

- 2. Dischargers are exempt from the requirements of (i)1 above during a calendar month in which they discharge no more than 15 kilograms of hazardous wastes, unless the wastes are acute hazardous wastes as specified in 40 CFR 261.30(d) and 261.33(e). Discharge of more than 15 kilograms of non-acute hazardous wastes in a calendar month, or of any quantity of acute hazardous wastes as specified in 40 CFR 261.30(d) and 261.33(e), requires a one-time notification. Additional notification is not required in subsequent months during which the indirect user discharges more than such quantities of any hazardous waste.
- 3. In the case of any new promulgated regulation under section 3001 of RCRA or the State's Solid Waste Management Act identifying additional characteristics of hazardous waste or listing any additional substance as a hazardous waste, the indirect user shall notify the local agency, the USEPA Regional Waste Management Waste Division Director, and the Division of Solid and Hazardous Waste of the discharge of such substance within 90 days of the effective date of such regulation.
- 4. In the case of any notification made under this subsection, the indirect user shall certify that it has a program in place to reduce the volume and toxicity of hazardous waste generated to the degree it has determined to be economically practical.
- (j) All indirect users shall promptly notify the local agency in advance of any

substantial change in the volume or character of pollutants in their discharge, including the listed or characteristic hazardous wastes for which the indirect user has submitted initial notification (i) above.

### 7:14A-21.4 Categorical standards, calculation of equivalent and/or alternative limits

- (a) When the categorical pretreatment standards are expressed in terms of production, equivalent effluent limitations shall be calculated as follows:
  - 1. When the limits in a categorical pretreatment standard are expressed only in terms of mass of pollutant per unit of production, the control authority may convert the limits to equivalent limitations expressed either as mass of pollutant discharged per day or effluent concentration for purposes of calculating effluent limitations applicable to individual indirect users.
  - 2. A control authority calculating equivalent mass-per-day limitations under (a)1 above shall calculate such limitations by multiplying the limits in the categorical pretreatment standard by the indirect user's average rate of production. This average rate of production shall be based not upon the designed production capacity but rather upon a reasonable measure of the indirect user's actual long-term daily production, such as the average daily production during a representative year. For new sources, actual production shall be estimated using projected production.
  - 3. A control authority calculating equivalent concentration limitations under (a)1 above shall calculate such limitations by dividing the mass limitations derived under (a)2 above by the average daily flow rate of the indirect user's regulated process wastewater. This average daily flow rate shall be based upon a reasonable measure of the indirect user's actual long-term average flow rate, such as the average daily flow rate during the representative year. For new sources, flow rate shall be estimated using projected flow rate.
  - 4. Equivalent limitations calculated in accordance with (a)2 and 3 above shall be deemed pretreatment standards for the purposes of section 307(d) of the Federal Act and this subchapter. Indirect users will be required to comply with the equivalent limitations in lieu of the promulgated categorical standards from which the equivalent limitations were derived.
  - 5. When a categorical pretreatment standard that specifies one limit for calculating maximum daily discharge limitations and a second limit for calculating maximum monthly average, or four-day average, limitations are applied, the same production or flow figure shall be

used in calculating both types of equivalent limitations.

- 6. Any indirect user operating under a control mechanism incorporating equivalent mass or concentration limits calculated from a production based standard shall notify the control authority within two business days after the indirect user has a reasonable basis to know that the production level will significantly change within the next calendar month. Any indirect user that does not notify the control authority of such anticipated change shall be required to meet the mass or concentration limits in its IPP permit that were based on the original estimate of the long term average production rate.
- (b) Except where expressly authorized to do so by an applicable pretreatment standard or requirement, no indirect user shall increase the use of process water, or in any other way attempt to dilute a discharge as a partial or complete substitute for adequate treatment to achieve compliance with a pretreatment standard or requirement. The control authority may impose mass limitations on indirect users which are using dilution to meet applicable pretreatment standards or requirements, or in other cases where the imposition of mass limitations is appropriate.
- (c) Where process effluent is mixed prior to treatment with wastewaters other than those generated by the regulated process, fixed alternative categorical limits shall be derived by the control authority or by the indirect user with the written concurrence of the control authority. These alternative categorical limits shall be applied to the mixed effluent. When deriving alternative categorical limits, the control authority or indirect user shall calculate both an alternative daily maximum value using the daily maximum value(s) specified in the appropriate categorical pretreatment standard(s) and an alternate monthly or consecutive sampling day average value using the monthly or consecutive sampling day average value(s) specified in the appropriate categorical pretreatment standard(s). The indirect user shall comply with the alternative categorical daily maximum and monthly average or consecutive sampling day limits fixed by the control authority, in the indirect user's permit. Modification is authorized whenever there is a material or significant change in the values used in the calculation to fix alternative categorical limits for the regulated pollutant. An indirect user shall immediately report any such material or significant change to the control authority. Where appropriate, alternative categorical limits shall be re-calculated within 30 days of being informed of changes by the indirect user.
  - 1. For purposes of these formulas, the average daily flow means a reasonable measure of the average daily flow for a 30-day period. For new sources, flows shall be estimated using projected values. The alternative limit for a specified pollutant shall be derived by the use of either of the following formulas:

i. Alternative concentration limit.

$$C_{T} = \frac{\sum_{i=1}^{N} C_{i} F_{i}}{\sum_{i=1}^{N} F_{i}} * \frac{F_{T} - F_{D}}{F_{T}}$$

where

C<sub>T</sub> = the alternative concentration limit for the combined wastestream.

Ci= the categorical pretreatment standard concentration limit for a pollutant in the regulated stream i.

Fi= the average daily flow (at least a 30-day average) of stream i to the extent that it is regulated for such pollutant.

 $F_{D}$  = the average daily flow (at least a 30-day average) from:

- (1) Boiler blowdown streams, non-contact cooling streams, stormwater streams, and demineralizer backwash streams, provided, however, that where such streams contain a significant amount of a pollutant, and the combination of such streams, prior to treatment, with an indirect user's regulated process wastestream(s) will result in a substantial reduction of that pollutant, the control authority, upon application of the indirect user, may exercise its discretion to determine whether such stream(s) shall be classified as diluted or unregulated. In its permit application to the control authority, the indirect user shall provide engineering, production, sampling and analysis and such other information so that the control authority can make its determination; or
- (2) Sanitary wastestreams where such streams are not regulated by a categorical pretreatment standard; or
- (3) From any process wastestreams which were or could have been entirely exempted from categorical pretreatment standards pursuant to paragraph 8 of the NRDC v. Costle Consent Decree (12 ERC 1833) for one or more of the following reasons:
  - (A) The pollutants of concern are not detectable in the effluent from the indirect user (paragraph (8)(a)(iii))

and/or as specified in the appropriate categorical standards;

- (B) The pollutants of concern are present only in trace amounts and are neither causing nor likely to cause toxic effects (paragraph (8)(a)(iii)) and/or as specified in the appropriate categorical pretreatment standards;
- (C) The pollutants of concern are present in amounts too small to be effectively reduced by technologies known to the Administrator (paragraph (8)(a)(iii)); or
- (D) The wastestream contains only pollutants which are compatible with the local agency's treatment works (paragraph (8)(b)(i)) and/or as specified in the appropriate categorical standards.
- $F_{_{\rm T}}$  = The average daily flow (at least a 30-day average) through the indirect user's treatment works (includes  $F_{_{\rm i}}$ ,  $F_{_{\rm D}}$  and unregulated streams).

N =The total number of regulated streams.

ii. Alternative mass limit.

$$\mathbf{M}_{T} = \sum_{i=1}^{N} \mathbf{M}_{i} * \frac{\mathbf{F}_{T} - \mathbf{F}_{D}}{\sum_{i=1}^{N} \mathbf{F}_{i}}$$

where

M<sub>T</sub> = the alternative mass limit for a pollutant in the combined wastestream.

 $M_i$  = the categorical pretreatment standard mass limit for a pollutant in the regulated stream i (the categorical pretreatment mass limit multiplied by the appropriate measure of production).

F<sub>i</sub> = the average flow (at least a 30-day average) of stream i to the extent that it is regulated for such pollutant.

 $F_{\rm D}$  = the average daily flow (at least a 30-day average) from:

(1) Boiler blowdown streams, non-contact cooling streams, stormwater streams, and demineralizer backwash streams,

provided, however, that where such streams contain a significant amount of a pollutant, and the combination of such streams, prior to treatment, with an indirect user's regulated process wastestream(s) will result in a substantial reduction of that pollutant, the control authority, upon application of the indirect user, may exercise its discretion to determine whether such stream(s) shall be classified as diluted or unregulated. In its permit application to the control authority, the indirect user shall provide engineering, production, sampling and analysis and such other information so that the control authority can make its determination; or

- (2) Sanitary wastestreams where such streams are not regulated by a categorical pretreatment standard; or
- (3) From any process wastestreams which were or could have been entirely exempted from categorical pretreatment standards pursuant to paragraph 8 of the NRDC v. Costle Consent Decree (12 ERC 1833) for one or more of the following reasons:
  - (A) The pollutants of concern are not detectable in the effluent from the indirect user (paragraph (8)(a)(iii)) and/or as specified in the appropriate categorical standards;
  - (B) The pollutants of concern are present only in trace amounts and are neither causing nor likely to cause toxic effects (paragraph (8)(a)(iii)) and/or as specified in the appropriate categorical standards;
  - (C) The pollutants of concern are present in amounts too small to be effectively reduced by technologies known to the Administrator (paragraph (8)(a)(iii)); or
  - (D) The wastestream contains only pollutants which are compatible with the local agency's treatment works (paragraph 8(b)(i)) and/or as specified in the appropriate categorical standards.
- $F_{_{\rm T}}$  = The average flow (at least a 30-day average) through the indirect user's treatment works (includes  $F_{_{\rm i}}$ ,  $F_{_{\rm D}}$  and unregulated streams).
- N =The total number of regulated streams.

- 2. An alternative pretreatment limit shall not be used if such alternative limit is below the analytical detection limit for any of the regulated pollutants.
- 3. The indirect user shall monitor, to ensure compliance with the alternative categorical limits, in accordance with the requirements of N.J.A.C. 7:14A-21.3(g).
- 4. Where a treated regulated process wastestream is combined prior to treatment with wastewaters other than those generated by the regulated process, the indirect user may monitor either the segregated process wastestream or the combined wastestream for the purpose of determining compliance with applicable pretreatment standards. If the indirect user monitors the segregated process wastestream, it shall apply the applicable categorical pretreatment standard. If the indirect user chooses to monitor the combined wastestream, it shall apply an alternative discharge limit calculated using the combined wastestream formula as provided in this section. The indirect user may change monitoring points only after receiving approval from the control authority. The control authority shall ensure that any change in an indirect user's monitoring point(s) will not allow the indirect user to substitute dilution for adequate treatment to achieve compliance with applicable standards.
- (d) Categorical pretreatment standards may be adjusted to reflect the presence of pollutants in the indirect user's intake water as follows:
  - 1. Any indirect user wishing to obtain credit for intake pollutants must submit a written request to the control authority. Upon such request, the applicable standard will be calculated on a "net" basis (that is, adjusted to reflect credit for pollutants in the intake water) if the requirements of (d)2 and 3 below are met.
  - 2. Criteria adjusting categorical pretreatment standards to reflect the presence of pollutants in the indirect user's intake water are as follows:
    - i. The indirect user shall demonstrate that the control system it proposes or uses to meet applicable categorical pretreatment standards would, if properly installed and operated, meet the standards in the absence of pollutants in the intake waters.
    - ii. Credit for generic pollutants such as biochemical oxygen demand (BOD), total suspended solids (TSS), and oil and grease shall not be granted unless the indirect user demonstrates that the constituents of the generic measure in the indirect user's effluent are substantially similar to the constituents of the generic measure in the intake water or unless appropriate additional

limits are placed on process water pollutants either at the outfall or elsewhere.

- iii. Credit shall be granted only to the extent necessary to meet the applicable categorical pretreatment standard(s), up to a maximum value equal to the influent value. Additional monitoring may be necessary to determine eligibility for credit and compliance with standard(s) adjusted under this section.
- iv. Credit shall be granted only if the indirect user demonstrates that the intake water is drawn from the same body of water as that into which the local agency's treatment works discharges. The control authority may waive this requirement if it finds that no environmental degradation will result.
- 3. The applicable categorical pretreatment standards contained in 40 CFR subchapter N specifically provide that they shall be applied on a net basis.

### 7:14A-21.5 Variance from categorical pretreatment standards for fundamentally different factors

- (a) Any interested person believing that factors relating to an indirect user are fundamentally different from the factors considered during development of a categorical pretreatment standard applicable to that indirect user and that the existence of those factors justifies a different discharge limit than specified in the applicable categorical pretreatment standard may request a fundamentally different factors variance under this section.
  - 1. A request for a variance based upon fundamentally different factors shall be approved only if:
    - i. There is an applicable categorical pretreatment standard which specifically controls the pollutant for which alternative limits have been requested;
    - ii. Factors relating to the discharge controlled by the categorical pretreatment standard are fundamentally different from the factors considered by USEPA in establishing the standards; and
    - iii. The request for a variance is made in accordance with the procedural requirements of (e) and (f) below.
  - 2. A variance request for the establishment of limits less stringent than required by the standard shall be approved only if:
    - i. The alternative limit requested is no less stringent than justified

by the fundamental difference;

- ii. The alternative limit will not result in a violation of any prohibition established under N.J.A.C. 7:14A-21.2(a)1;
- iii. The alternative limit will not result in a non-water quality environmental impact (including energy requirements) fundamentally more adverse than the impact considered during development of the pretreatment standards; and
- iv. Compliance with the standards (either by using the technologies upon which the standards are based or by using other control alternatives) would result in either:
  - (1) A removal cost (adjusted for inflation) wholly out of proportion to the removal cost considered during development of the standards; or
  - (2) A non-water quality environmental impact (including energy requirements) fundamentally more adverse than the impact considered during development of the standards.
- 3. A variance request for the establishment of limits more stringent than required by the standards shall be approved only if:
  - i. The alternative limit request is no more stringent than justified by the fundamental difference; and
  - ii. Compliance with the alternative limit would not result in either:
    - (1) A removal cost (adjusted for inflation) wholly out of proportion to the removal cost considered during development of the standards; or
    - (2) A non-water quality environmental impact (including energy requirements) fundamentally more adverse than the impact considered during development of the standards.
- (b) Factors which may be considered fundamentally different are:
  - 1. The nature or quality of pollutants contained in the raw waste load of the indirect user's process wastewater:
  - 2. The volume of the indirect user's process wastewater and effluent discharged;
  - 3. The non-water quality environmental impact of control and treatment of the indirect user's raw waste load;

- 4. The energy requirements of the application of control and treatment technology;
- 5. The age, size, land availability, and configuration as they relate to the indirect user's equipment or facilities, processes employed, process changes, and engineering aspects of the application of control technology; and
- 6. The cost of compliance with required control technology.
- (c) A variance request or portion of such a request under this section shall not be granted on any of the following grounds:
  - 1. The feasibility of installing the required waste treatment equipment within the time the Act allows;
  - 2. The assertion that the standards cannot be achieved with the appropriate waste treatment facilities installed, if such assertion is not based on factors listed in (b) above;
  - 3. The indirect user's ability to pay for the required waste treatment; or
  - 4. The impact of a discharge on the quality of the local agency's receiving waters.
- (d) Nothing in this section shall be construed to impair the right of any local agency to impose more stringent limitations than required by Federal law.
- (e) Requests for a variance and supporting information shall be submitted in writing to the Department no later than 180 days after the date on which a categorical pretreatment standard is published in the <u>Federal Register</u> for a request based on a categorical pretreatment standard promulgated on or after February 4, 1987.
  - 1. Where the indirect user has requested a categorical determination pursuant to N.J.A.C. 7:14A-21.3(a), the indirect user may elect to await the results of the categorical determination before submitting a variance request under this section. Where the indirect user so elects, he or she must submit the variance request within 30 days after a final decision has been made on the categorical determination.
- (f) Written variance requests shall include:
  - 1. The name and address of the person making the request;
  - 2. Identification of the interest of the requester which is affected by the categorical pretreatment standard for which the variance is requested;

- 3. Identification of the local agency currently receiving the waste from the indirect user for which alternative discharge limits are requested;
- 4. Identification of the categorical pretreatment standards which are applicable to the indirect user;
- 5. A list of each pollutant or pollutant parameter for which an alternative discharge limit is sought;
- 6. The alternative discharge limits proposed by the requester for each pollutant or pollutant parameter identified pursuant to (f)5 above;
- 7. A description of the indirect user's existing water pollution control facilities;
- 8. A schematic flow representation of the indirect user's water system including water supply, process wastewater systems, and points of discharge; and
- 9. A statement of facts clearly establishing why the variance request should be approved, including detailed support data, documentation, and evidence necessary to fully evaluate the merits of the request, e.g., technical and economic data collected by the USEPA and used in developing each pollutant discharge limit in the pretreatment standard.
- (g) The Department shall act only on written requests for variances that contain all of the information required pursuant to (f) above. Persons who have made incomplete submissions will be notified by the Department that their requests are deficient and unless the time period is extended, will be given up to 30 days to remedy the deficiency. If the deficiency is not corrected within the time period allowed by the Department, the request for a variance shall be denied.
- (h) Upon receipt of a complete request, the Department shall provide public notice of receipt, opportunity to review the submission, and opportunity to comment.
  - 1. The public notice shall be published in a manner designed to inform interested and potentially interested persons of the request, and. shall include mailing notices to:
    - i. The local agency into whose treatment works the indirect user requesting the variance discharges;
    - ii. Adjoining states whose waters may be affected;
    - iii. Agencies responsible for areawide Water Quality Management Plan, Federal and State fish, shellfish and wildlife resource

agencies; and

- iv. Any other person or group who has requested individual notice, including those on appropriate mailing lists.
- 2. The public notice shall provide for a period not less than 30 days following the date of the public notice during which time interested persons may review the request and submit written comments on the request.
- 3. Following the comment period, the Department will make a determination on the request, taking into consideration any comments received. Notice of this final decision shall be provided to the requester and the indirect user for which the variance is requested, if different, the local agency into whose treatment works the indirect user discharges and all persons who submitted comments on the request.
- (i) Review of requests by the Department is as follows:
  - 1. Where the Department finds that fundamentally different factors do not exist, it shall deny the request and notify the requester (and indirect user where they are not the same) and the local agency of the denial.
  - 2. Where the Department finds that fundamentally different factors do exist, it shall forward the request, with a recommendation that the request be approved, to the USEPA Administrator. (Review of the variance request by USEPA is governed by 40 CFR Part 403.13(l)).
- (j) Requests for an adjudicatory hearing shall be as follows:
  - 1. If the Department denies the variance request, the requester may request an adjudicatory hearing pursuant to N.J.A.C. 7:14A-17.
  - 2. If USEPA denies the variance request, the requester may seek relief pursuant to 40 CFR Part 403.13(m).

#### 7:14A-21.6 Bypass

- (a) An indirect user may allow any bypass to occur which does not cause pretreatment standards to be violated, but only if such bypass is for essential maintenance to ensure efficient operation. Such bypasses are not subject to (b) and (c) below.
- (b) Notice of bypass shall be as follows:
  - 1. If an indirect user knows in advance of the need for a bypass, it shall submit prior notice to the control authority, if possible at least 10 days

before the date of the bypass.

- 2. An indirect user shall inform the control authority by telephone or in person of an unanticipated bypass that exceeds applicable pretreatment standards within 24 hours from the time the indirect user becomes aware of the bypass. A written submission shall also be provided within five days of the time the indirect user becomes aware of the bypass. The written submission shall contain a description of the bypass and its cause; the duration of the bypass, including exact dates and times, and, if the bypass has not been corrected, the anticipated time it is expected to continue; and steps taken or planned to reduce, eliminate, and prevent reoccurrence of the bypass. The control authority may waive the written report on a case-by-case basis if the information of the bypass by telephone or in person was received within 24 hours of the indirect user's becoming aware of the bypass.
- (c) Bypass is prohibited, and the control authority may take enforcement action against an indirect user for a bypass, unless:
  - 1. Bypass was unavoidable to prevent loss of life, personal injury, or severe property damage;
  - 2. There were no feasible alternatives to the bypass, such as the use of auxiliary treatment facilities, retention of untreated wastes, or maintenance during normal periods of equipment downtime. This condition is not satisfied if adequate back-up equipment should have been installed in the exercise of reasonable engineering judgment to prevent a bypass which occurred during normal periods of equipment downtime or preventive maintenance; and
  - 3. The indirect user notified the control authority as required under (b) above.
- (d). The control authority may approve an anticipated bypass, after considering its adverse effects, if the control authority determines that it will meet the conditions in (c)1 through 3 above.

# 7:14A-21.7 Additional requirements for facilities which meet the SIU definition and discharge to a delegated local agency's treatment works

Any indirect user which meets the SIU definition in N.J.A.C. 7:14A-1.2 and discharges or plans to discharge to a delegated local agency's treatment works shall obtain an IPP permit from that delegated local agency. Delegated local agencies are required pursuant to N.J.A.C. 7:14A-19.3(c)2 to issue IPP permits to such indirect users.

## 7:14A-21.8 Additional requirements for facilities which meet the SIU definition and discharge to a non-delegated local agency's treatment works

An indirect user which meets the SIU definition in N.J.A.C. 7:14A-1.2 and discharges or plans to discharge to a local agency which is not a delegated local agency as defined at N.J.A.C. 7:14A-1.2 shall obtain an individual NJPDES-SIU permit from the Department pursuant to N.J.A.C. 7:14A-2.4 and 7:14A-4.

## 7:14A-21.9 Exemptions from the requirements for an individual NJPDES-SIU permit from the Department

- (a) An indirect user authorized to discharge by the local agency is exempt from the requirement to obtain an individual NJPDES-SIU permit from the Department if:
  - 1. The indirect user does not meet the SIU definition; or
  - 2. The indirect user discharges to a delegated local agency's treatment works.
- (b) The Department may, at its discretion, revoke a NJPDES-SIU permit if the permittee meets the exemption criteria of (a) above.
- (c) A permittee may request revocation of an individual NJPDES-SIU permit by submitting to the Department a certification by an authorized representative of the permittee stating the date and describing in detail when and why the permittee became eligible for an exemption pursuant to (a) above.
- (d) The Department shall revoke the NJPDES-SIU permit if the permittee establishes pursuant to (c) above that the permittee qualifies for an exemption under (a) above.
- (e) The terms and conditions of the individual NJPDES-SIU permit, including, but not limited to, the requirement to file a timely application for permit renewal, remain in full force and effect unless and until such permit is revoked consistent with the procedures in N.J.A.C. 7:14A-16.
- (f) If an individual NJPDES-SIU permit is revoked pursuant to this section, the user may continue to discharge and shall comply with any pretreatment requirements of the local agency and this subchapter.

# 7:14A-21.10 Establishing conditions and effluent limitations for an individual NJPDES-SIU permit issued by the Department

(a) Effluent limitations for NJPDES-SIU permits shall be developed for the applicable pollutants based on one or more of the following:

- 1. Applicable or relevant categorical pretreatment standards under 40 CFR Chapter I, Subchapter N, calculated and/or adjusted if applicable in accordance with N.J.A.C. 7:14A-21.4;
- 2. Local limits developed in accordance with N.J.A.C. 7:14A-19.7;
- 3. In the absence of local limits developed by the local agency in accordance with N.J.A.C. 7:14A-19.7, limitations will be calculated by the Department to prevent pass through or interference at the receiving local agency's treatment works using the <u>Guidance Manual on the Development and Implementation of Local Discharge Limitations Under the Pretreatment Program</u>, USEPA, (December 1987);
- 4. Limitations based upon performance of existing and proposed wastewater pretreatment units; and
- 5. Minimum requirements for all indirect users of local agencies specified in N.J.A.C. 7:14A-21.2.
- (b) In addition to effluent limitations, the individual NJPDES-SIU permit shall contain the following conditions, requirements and/or provisions, as applicable:
  - 1. Reporting and filing requirements in accordance with N.J.A.C. 7:14A-21.3;
  - 2. Slug discharge control plan requirements as specified in N.J.A.C. 7:14A-19.6(a)7.
  - 3. Residuals management requirements pursuant to N.J.A.C. 7:14A-6.15;
  - 4. Treatment Works Approval requirements such as proper maintenance and operation of the pretreatment system and, licensed operator requirements in accordance with N.J.A.C. 7:14A-22;
  - 5. Compliance schedule pursuant to N.J.A.C. 7:14A-6.4(a); and
  - 6. Bypass provisions pursuant to N.J.A.C. 7:14A-21.6.

#### 7:14A-21.11 Violations; closing off of use of sewerage connections

(a) The Department or the local agency may, in instances of indirect user non-compliance, take such steps as may be necessary to seal or close off connections from the local agency to the indirect user until it is satisfied that adequate measures have been taken to prevent the recurrence of non-compliance in accordance with N.J.S.A. 58:11-56.